


3. SPOJNI PRIBOR General hardware

3.9. Zatvarači

Zatvarač užni zatvoreni CWS

Closed wedge socket CWS type

Min. prekidna sila (Mt)	Za užje promjera (mm)	A (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	X (mm)	Težina (kg/kom)
MBL	For rope dia.								Weight
40	17-19	317	40	36	100	42	277	100	7
55	20-22	368	45	40	115	50	323	110	9
80	23-26	422	52	45	130	60	370	125	14
100	27-29	473	58	50	150	65	415	140	22
120	30-32	519	62	55	160	72	457	160	30
130	34-36	580	66	60	168	76	514	175	38
160	37-39	620	72	66	175	82	548	190	49
200	40-42	665	80	72	195	90	585	210	65
250	43-48	750	90	80	220	100	660	240	110
300	49-52	820	100	90	242	110	720	260	140
375	54-58	890	106	95	255	120	784	280	170
450	60-68	1045	120	105	280	130	925	330	240
600	72-76	1200	140	120	330	150	1060	400	380
650	81-86	1340	155	130	375	170	1185	475	490



2.1 2.2 CE




• EN 13411-6

Zatvarač užni za zalijevanje APS

Anchor pendant socket

Min. prekidna sila (Mt)	Za užje promjera (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	Ø H (mm)	Ø K (mm)	Težina (kg/kom)
MBL	For rope dia.										Weight
130	31-36	270	141	88	40	36	140	82	41	60	7
160	37-42	309	162	103	44	40	152	92	46	67	11
200	43-48	369	193	123	53	48	176	110	56	74	16
250	49-54	408	210	140	58	52	200	125	58,5	83	22
320	55-60	452	230	157	65	58	226	140	68	96	31
400	61-68	499	250	174	75	66	250	156	76	107	42
500	69-75	551	280	191	80	70	275	171	80	115	54
600	76-80	591	309	196	86	76	290	180	89	125	70
700	81-86	643	332	211	100	90	304	188	94	133	85
800	87-93	685	360	220	105	95	332	210	99	142	118
900	94-102	722	375	235	112	101	366	220	110	157	142
1000	108-115	818	420	270	126	112	405	240	128	180	180
1200	120-128	920	490	290	140	126	450	276	140	200	320



2.1 2.2 CE

