

6. EL. DIZALICE, VITLA I VILIČARI El. hoists, forklifts

6.1. Električne dizalice i vitla

RX-lift

Dizalica električna građevinska tip PA RX-lift

Mini electric hoist type PA RX-lift

2.1 2.2 CE



- EN 14492-2
- klasa zaštite: IP 54



* dostupna električna i ručna kolica za PA dizalice

Model HGS-B	Korištenje Method of use	Ulazna snaga (W) Input power	Nosivost (kg) Rated capacity	Brzina dizanja (m/min) Lifting speed	Visina dizanja (m) Lifting height	Bruto/ neto težina (kg) Gross/ net weight	Dimenzija pakiranja (mm) Packing size
PA 200	Jednostruko	480	100	10	12	24/22	490x425x155
PA 200	Preko koloture	480	200	5	6	24/22	490x425x155
PA 250	Jednostruko	540	125	10	12	24/22	490x425x155
PA 250	Preko koloture	540	250	5	6	24/22	490x425x155
PA 300	Jednostruko	600	150	10	12	24/22	490x425x155
PA 300	Preko koloture	600	300	5	6	24/22	490x425x155
PA 400	Jednostruko	950	200	10	12	36/34	525x480x165
PA 400	Preko koloture	950	400	5	6	36/34	525x480x165
PA 500	Jednostruko	1020	250	10	12	36/34	525x480x165
PA 500	Preko koloture	1020	500	5	6	36/34	525x480x165
PA 600	Jednostruko	1200	300	10	12	36/34	525x480x165
PA 600	Preko koloture	1200	600	5	6	36/34	525x480x165
PA 700	Jednostruko	1250	350	8	12	38/36	540x505x170
PA 700	Preko koloture	1250	700	4	6	38/36	540x505x170
PA 800	Jednostruko	1300	400	8	12	38/36	540x505x170
PA 800	Preko koloture	1300	800	4	6	38/36	540x505x170
PA 990	Jednostruko	1600	500	8	12	33/32	620x240x350
PA 990	Preko koloture	1600	990	4	6	33/32	620x240x350

Konzola okretna za el. građevinsku dizalicu tip PA RX-lift

Console for mini electric hoist type PA RX-lift

2.1

Kapacitet (t) Rated capacity	Radna dužina (m) Working length
250	1100
600	750

