

3. SPOJNI PRIBOR General hardware

3.3. Jezgre

Jezgra DIN 3091 / EN 13411-9 RX-lift

Thimble acc. to DIN 3091 RX-lift

Promjer užeta (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Težina (kg/100 kom)
Wire rope diameter							Weight
8	9	15	40	66	14	–	18
10	11	17,5	50	82	18	–	32
12	13	20	60	98	21	–	52
14	16	23,5	70	114	25	–	80
16	18	26	80	130	28	16	90
18	20	28,5	90	145	31	18	121
20	22	31	100	161	35	20	161
22	24	33,5	110	177	38	22	211
24	26	36	120	193	41	24	271
26	29	39,5	130	209	44	26	355
28	31	42	140	224	47	28	420

Promjer užeta (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	Težina (100 kom/kg)
Wire rope diameter							Weight
32	35	47	160	256	53	32	630
36	40	53	180	288	59	36	884
40	44	58	200	320	65	40	1.100
44	48	63	220	352	70	44	1.500
48	53	69	240	384	76	48	2.000
52	57	74	260	416	81	52	2.500
56	62	80	280	448	86	56	3.200
64	70	90	320	512	95	64	4.600
72	79	101	360	576	104	72	6.600
80	88	112	400	640	112	80	9.000

